

war

A war package

Table of contents

1 Overview.....	2
2 Design.....	2
3 Constraints.....	2
3.1 Allowed Property Values.....	2
4 Commands.....	2
4.1 create.....	2
4.2 extract.....	3

1. Overview

war: *A war package*

2. Design

Super Type Package

Role	Concrete. (Objects can be created.)
Instance Names	Unique
Notification	false
Template Directory	
Data View	Children, proximity: 1
Logger Name	war

3. Constraints

3.1. Allowed Property Values

Property	Allowed Values	Default	Enforced
package-filetype	• war	• war	true
package-repo-url	• <code>\${framework.pkg}</code>	• <code>\${framework.pkg}</code>	false
package-vendor	• acme	• acme	false

4. Commands

Note:

Commandline options displayed in square brackets "[]" are optional. If an option expects arguments, then angle brackets are shown after the option "<>". Any default value is shown within the brackets.

4.1. create

creates a package archive

war

Usage

```
create [-filename <>] [-installroot <>] -webxml <>
```

4.1.1. Options

Option	Description
filename	<i>file to write archive</i>
installroot	<i>root where source files reside</i>
webxml	<i>The deployment descriptor to use (WEB-INF/web.xml).</i>

4.2. extract

extracts the package

Extracts the web archive file into the install root directory. If `-base` is also specified, the extraction will occur in `${opts.installroot}/${opts.base}`.

Usage

```
extract [-base <>] [-filename <>] [-installroot <>]
```

4.2.1. Options

Option	Description
base	<i>package base name</i>
filename	<i>file to extract</i>
installroot	<i>destination directory</i>