

Object-Create

Table of contents

1 Description.....	2
2 Parameters.....	2
3 Parameters specified as nested elements.....	2
4 Examples.....	2

1. Description

Creates a new object in specified project.

2. Parameters

Attribute	Description	Required
depot	The project to update	Yes
resultproperty	Property to set with success/fail value	Yes
comment	Text describing purpose of update	Yes
passfile	File containing authentication info to server. If passfile is not specified, information from the framework.properties file is used instead.	No

3. Parameters specified as nested elements

setting

A [setting](#) object.

deployment

A [deployment](#) object.

assembly

A [assembly](#) object.

node

A [node](#) object.

package

A [package](#) object.

4. Examples

Create a package object.

```
<object-create depot="${context.depot}"
              resultproperty="result"
              comment="Created package object from command">
  <package
    name="${rpm.name}"
    type="Package"
    description="${rpm.descr}"
    filename="${rpm.filename}"
    version="${rpm.version}"
    release="${rpm.release}"
    base="${rpm.base}"
    arch="${rpm.arch}"
    vendor="${rpm.vendor}"
    buildtime="${rpm.buildtime}"/>
</object-create>
<condition property="wasCreated">
  <equals arg1="0" arg2="${result}"/>
</condition>
<fail unless="wasCreated">Failed saving object.</fail>
```